

## Amended Patent Claims

1. (original) A method of rolling and then coiling metal strip (1), especially steel strip (1) on at least one drivable spreadable coiling mandrel or core (20), whereby the metal strip (1) is inspected in longitudinal segments for rolling anomalies, characterized in that the strip samples (1a) within the rolling line (2a) are guided "in line" over a coiling station (18) located below the strip samples onto an inspection table (11) for a free viewing or perusal and stopped thereon.

2. (currently amended) The method according to ~~one of claims 1 or 2~~ ~~[sic]~~ claim 1, characterized in that after cutting the strip sample (1a) from the oncoming continuous rolled strip, the new strip leading end is deflected downwardly below the inspection table (11) and wound on an upper coiling mandrel (20) or a lower coiling mandrel (21) [of the coiling station (18)] lying below the inspection table (1).

3. (original) The method according to claim 2, characterized in that the strip samples (1a) are braked on the inspection table (11) by a belt conveyor (17) integrated in the inspection table (11).

4. (currently amended) The method according to ~~one of~~  
~~claims 1 to 3~~ claim 1, characterized that a wound coil (25) wound  
upon the upper coiling mandrel (20) is swung through 180° during  
the continuous rolling operation and is finish wound to a  
predetermined maximum coil diameter (25a).

5. (currently amended) The method according to ~~one of~~  
~~claims 1 to 4~~ claim 1 characterized in that a wound coil 25 wound  
upon the lower coiling mandrel 21 is lowered and carried off  
parallel to the coiling mandrel axis.

6. (original) An apparatus for rolling and then coiling  
metal strip  
(1), especially steel strip (2), wherein downstream of a rolling  
line and connected to the last rolling mill stand (2) an  
inspection device is arranged for inspecting the metal strip (2)  
for rolling anomalies, characterized in that the coiling station  
(18) is located below the plane of an inspection table (11)  
running "in line" to the rolling line (2a) and upon which a strip  
sample (1a) can be freely perused.

7. (original) The apparatus according to claim 6  
characterized in that at the inlet (27) to the coiling station 18 a  
deflection unit (10) is provided for deflecting the metal strip (1)  
to at least one coiling mandrel (20; 21).

8. (currently amended) The apparatus according to ~~one of claims 6 or 7~~ claim 6, characterized in that the coiling station(18) is constructed of a respective upper coiling mandrel (20) and lower coiling mandrel (21) arranged eccentrically within a rotating frame (28) below the plane of the inspection table (11).

9. (original) The apparatus according to claim 8 characterized in that the upper coil mandrel (20) and the lower coil mandrel (21) lie on a diameter through the control axis (28a) of the rotating frame (28).


10. (currently amended) The apparatus according to ~~one of claims 7 or 8~~ claim 7 characterized in that the diameter runs at an angle to the horizontal of about 15° to 25°.

11. (currently amended) The apparatus according to ~~one of claims 6 to 10~~ claim 6 characterized in that the rotating frame (28) for the coiling mandrels (20; 21) is journaled for rotation on rotatably driven support rollers (2a).

12. (currently amended) The apparatus according to ~~one of claims 6 to 11~~ claim 6 characterized in that the lower coiling mandrel (21) has juxtaposed with it a pressing roller arm (30) swingable in and out and provided with a pressing roller (31).

This preliminary amendment is submitted to provide the cross reference of the present US phase of PCT application PCT/EP2003/014938 to the international application according to Rule 78 and to eliminate multiple dependencies in the claims.

Respectfully submitted,  
The Firm of Karl F. Ross P.C.



---

By: Herbert Dubno, Reg. No. 19,752  
Attorney for Applicant

18 May 2005  
5676 Riverdale Avenue Box 900  
Bronx, NY 10471-0900  
Cust. No.: 535  
Tel: (718) 884-6600  
Fax: (718) 601-1099

rg